



41FT REFRIGERATED
CONTAINER

41ft Refrigerated Container

SCF's 41ft 20 pallet
Refrigerated container
delivers superior
temperature control for up
to 40 pallets (with load bars).
Intelligent insulation design
provides optimum
refrigeration properties to
reduce machinery run time,
fuel consumption and costs.

Key Features

- Thermo King or Carrier electric machinery
- 2 pallet wide up to 40 pallets with vertical load bars
- Custom SCF insulation design for premium thermal performance
- Vertical load bars for double stacking
- F-track for freight restraint
- Airflow floor design for efficient cooling
- Internal scuff plates and flush mounted components to reduce damage

Options

- Motor type TK or Carrier
- Remote temperature control and GPS Tracking
- Lightweight Model
- Branding

Details

SCF's 41 foot refrigerated container can store up to 40 pallets in a temperature controlled environment with the utilisation of our internal load bars and double stacking.

Built with superior temperature control and insulation, temperature is efficiently maintained with reduced machinery run time, reducing fuel consumptions and costs.

SCF is a supplier to Australia's leading logistics companies coupled with our +25 years experience, we fully understand the importance of reliable, economical and fail-safe refrigeration.

Our range of refrigerated shipping containers are designed specifically with the end user in mind and offer flexibility in capacity options and sizes to suit your requirements.

Specifications

Payload (kg)

MGW (kg)

28,200

35,000

41ft Refrigerated Container | R4191

Specifications may vary

Internal		External	
Length (mm)	11,780	Length (mm)	12,573
Width (mm)	2,385	Width (mm)	2,500
Height (mm)	2,716	Height (mm)	3,000
Weight			
Tare (kg)	6,400		



Top: SCF's 41ft Refrigerated Container is built with super thermal properties to reduce machinery run time.

Middle Left: We offer short and long-term hire options to suit your requirements.

Middle Right: Vertical Load Bars enable the user to store up to 40 pallets in a temperature controlled environment.

Below: Highlighted pickup points make it easier and safer to lift.





